



- NOTES:**
1. MATERIAL: ASTM-A-366 12 (0.1046") GAGE STEEL
 2. CLEAR ZINC PLATE, ASTM-B633 TYPE 2 SC 4.
 3. DEBURR AND REMOVE SHARP EDGES.
 4. WRAP INDIVIDUALLY.
 5. DXF FDMAT AVAILABLE ON REQUEST.
 6. STAMP PART NUMBER AND REV. IN APPROXIMATE LOCATION SHOWN ON NEAR SIDE.

| PART NUMBER LIST | |
|------------------|---|
| 622-UBRKT/C61B | BLACK: POLYESTER TGIC POWDER COATING FINE TEXTURE, CARDINAL C241-BK01 FED STD 27038 FS#27038 20%-25% GLOSS, OR EQUIV. MAX E ON A COLORIMETER NOT TO EXCEED 1.99 |
| 622-UBRKT/C61W | WHITE: POLYESTER TGIC POWDER COATING FINE TEXTURE, CARDINAL: RAL 9010, T041-WH371 WHITE TEXTURE 20% GLOSS OR EQUIV. MAX E ON A COLORIMETER NOT TO EXCEED .199 |

THE MATERIAL CONTAINED HEREIN IS PROPRIETARY TO RENKUS-HEINZ AND SHALL NOT BE REPRODUCED DISCLOSED OR USED FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN APPROVAL OF RENKUS-HEINZ.

| ECD | REV | DESCRIPTION | DATE | BY |
|------|-----|--|----------|----|
| 8382 | B | OBRUND DIM .43" [11.0mm] WAS .4 [10.16mm]; DEL CAD PLATE FINISH; ZINC PLATE WAS TYPE 3 SC 2. | 10/3/17 | LB |
| 8382 | C | REV'D P/N LIST TO CURRENT PAINT TEXTURE/GLOSS STDS. | 6/10/21 | GL |
| 8915 | D | UPDATED TO INCLUDE HEM DETAILS | 12/07/21 | DL |

| | | | | |
|---|-------------------------------|----------------------|---------|---|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: | DRAWN | INTL | DATE | RENKUS-HEINZ, inc. TITLE: U-BRACKET, C(X)61 |
| DECIMALS .XX±.01 .XXX±.005 | CHECK | J.D. | 3-29-17 | |
| ANGLES ±0° 30' | DESIGN | | | |
| | ENG | | | |
| | APPROV | | | |
| | APPROV | | | |
| | REF DWG: | | | |
| | 622-UBRKT-C61-D.DWG | | | |
| NEXT ASSY. | USED ON | DD NOT SCALE DRAWING | SIZE | CODE IDENT |
| APPLICATION | DEBURR AND REMOVE SHARP EDGES | SCALE 1 = 1 | WEIGHT | DWG NO. |
| | | | | 622-UBRKT/C61 |
| | | | | REV |
| | | | | D |
| | | | | SHEET 1 OF 1 |